



COMMODORE
OFF GRID & SOLAR PUMPING SPECIALISTS

COMMODORE

GENERATORS



MAIN OFFICE (VIC)
1300 669 256

NEW SOUTH WALES
02 4018 3502

QUEENSLAND
07 3123 6688

WESTERN AUSTRALIA
08 6365 1790

SOUTH AUSTRALIA
08 7562 9416

TASMANIA
03 6111 0649

ACT
02 4018 3502

NORTHERN TERRITORY
08 7562 9416



COMMODORE
OFF GRID & SOLAR PUMPING SPECIALISTS



Commodore Generators

Automatically give charge to your off-grid system, or integrate a switch to provide your on-grid home blackout protection with a Commodore Generator. Available in air-cooled or water-cooled, and single or three-phase, Commodore Generator's are built to last with all water-cooled models including a 3 + 1-year warranty (the additional year when purchased with a Commodore off-grid system) and 1 year on the 5.7KVA air-cooled model.



MODEL	5.7KVA	9.3KVA	11KVA	13.2KVA	16.5KVA
Phase	Single	Single	Three	Single	Three
Voltage	240V	240V	415V	240V	415V
Type	Air-Cooled	Water-Cooled	Water-Cooled	Water-Cooled	Water-Cooled
Standby Output	5.7KVA	9KVA	11KVA	13.2KVA	16.5KVA
Continuous Output	5.2kW	8.5kW	10kW	12kW	15kW
Frequency	50Hz	50hZ	50hZ	50hZ	50hZ
Power Factor	1:1	1:1	0.8	1:1	0.8
Noise	70DbA @ 7m	69DbA @ 7m	69DbA @ 7m	69DbA @ 7m	69DbA @ 7m
Cylinders	1 NA	3 NA	3 NA	4 NA	4 NA
Engine Speed	3000RPM	1500RPM	1500RPM	1500RPM	1500RPM
Displacement	474cc	1.532L	1.532L	2.27L	2.27cc
Oil Capacity	1.65L	5.5L	5.5L	7.8L	7.8L
Fuel Capacity	14L	35L	35L	40L	40L
Coolant Capacity	N/A	5.8L	5.8L	5.8L	5.8L
Fuel Usage @ 100%	2.1L/H	3.4L/H	3.4L/H	4.9L/H	5L/H
Fuel Usage @ 50%	1.2/H	1.7L/H	1.7L/H	2.5L/H	2.5L/H
L x W x H	960 x 540 x 770	1620 x 750 x 750	1720 x 750 x 750	1800 x 750 x 850	1800 x 750 x 850
Weight	162kg	480kg	485kg	615kg	598kg
Controller	Smart Gen	Deep Sea	Deep Sea	Deep Sea	Deep Sea
Remote Start	2 Wire	2 Wire	2 Wire	2 Wire	2 Wire



COMMODORE
OFF GRID & SOLAR PUMPING SPECIALISTS



Commodore Generators

Automatically give charge to your off-grid system, or integrate a switch to provide your on-grid home blackout protection with a Commodore Generator. Available in air-cooled or water-cooled, and single or three-phase, Commodore Generator's are built to last with all water-cooled models including a 3 + 1-year warranty (the additional year when purchased with a Commodore off-grid system) and 1 year on the 5.7KVA air-cooled model.



MODEL	17.6KVA	22KVA	27.5KVA	44KVA	62KVA
Phase	Single	Three	Three	Three	Three
Voltage	240V	415V	415V	415V	415V
Type	Water-Cooled	Water-Cooled	Water-Cooled	Water-Cooled	Water-Cooled
Standby Output	17.6KVA	22KVA	27.5KVA	44KVA	62KVA
Continuous Output	16kW	20kW	25kW	40kW	56kW
Frequency	50Hz	50hZ	50hZ	50hZ	50hZ
Power Factor	1:1	0.8:1	0.8:1	0.8:1	0.8
Noise	69DbA @ 7m	69DbA @ 7m	75DbA @ 7m	70DbA @ 7m	71DbA @ 7m
Cylinders	4 NA	4 NA	4 T	4 T	4 T
Engine Speed	1500RPM	1500RPM	1500RPM	1500RPM	1500RPM
Displacement	2.16cc	2.54L	2.16L	3.9L	3.9L
Oil Capacity	7.8L	7.8L	7.8L	11L	10.9L
Fuel Capacity	40L	40L	40L	80L	90L
Coolant Capacity	5.8L	5.8L	5.8L	7.2L	7.9
Fuel Usage @ 100%	6.2L/H	6L/H	7.3L/H	9.3L/H	13.1L/H
Fuel Usage @ 50%	3L/H	3L/H	3.65L/H	4.65L/H	6.55L/H
L x W x H	1800 x 750 x 850	1800 x 750 x 850	1800 x 800 x 850	2250 x 960 x 1200	2250 x 960 x 1200
Weight	642kg	616kg	662kg	946kg	1141kg
Controller	Deep Sea	Deep Sea	Deep Sea	Deep Sea	Deep Sea
Remote Start	2 Wire	2 Wire	2 Wire	2 Wire	2 Wire